

# TortillaTek®

## MAX READY-TO-USE NON-STICK LIQUID TEFLÓN

### PRODUCT DESCRIPTION:



TortillaTek® MAX Ready-To-Use (RTU) non-stick liquid teflón is NOT AN INGREDIENT or an ADDITIVE. It is a processing aid developed to meet the needs of tortilla, wrap, flat-bread, and chapatti manufactures, etc. eliminate product sticking to their slat belts without effecting the taste, smell & quality of their products creating a minimal amount of thermal build-up on their slat belts.

### INSTRUCTIONS:



### SHAKE WELL BEFORE USING



1. Clean your slat belts daily using a soft cloth/brush before turning on oven burners
2. **NOTE:** Agitate diluted teflón approximately 60 to 90 seconds before applying
3. Apply TortillaTek® MAX Ready-To-Use teflón using a common spray bottle, air gun, etc. evenly over entire top & middle slat belt surface while oven is between 50°F & 200°F (98°C)
4. The time between re-applying teflón applications varies from \*6 to \*12 hours of production depending on oven length, speed, temperature, slat belt condition, product size and weight, etc.

**INGREDIENTS:** polydimethyl siloxane, emulsifier, sodium benzoate and water

**Precautionary Statements:** P305+P338, P351, P301+P330+331

**Hazard Statement:** None specific

**Accidental eye contact:** Rinse thoroughly with water for several minutes. Remove contact lenses, if present and continue rinsing.



**Available in 5 US Gal. pails (18.9 L.)**

**SAFETY FIRST  
RECOMMENDED PPE  
PERSONAL PROTECTIVE EQUIPMENT**



**Distributed by: Tortillaworld, Inc.**  
P.O. Box 346  
Plainfield, Illinois, 60544  
1-800-335-Tortilla (8678) ext. 101  
Direct/WhatsApp: 773-882-2308  
[www.tortillaworld.com](http://www.tortillaworld.com)

