

TortillaTek®

MAX CONCENTRATED NON-STICK LIQUID TEFLÓN

PRODUCT DESCRIPTION:



TortillaTek® MAX concentrated non-stick liquid teflón is NOT AN INGREDIENT or an ADDITIVE. It is a processing aid developed to meet the needs of tortilla, wrap, flat-bread, and chapatti manufactures, etc. eliminate product sticking to their slat belts without effecting the taste, smell & quality of their products creating a minimal amount of thermal build-up on their slat belts.

INSTRUCTIONS



SHAKE WELL BEFORE USING

1. Clean your slat belts daily using a soft cloth/brush before turning on oven burners
2. **NOTE:** Minimum dilution ratio for **MAX** concentrated teflón is 6 to 1. 6 parts water to 1 of teflón, up to *12 to 1. Agitate diluted teflón approximately 60 to 90 seconds before applying
3. Apply TortillaTek® MAX concentrated teflón using a common spray bottle, air gun, etc. evenly over entire top & middle slat belt surface while oven is between 50°F & 200°F (98°C)
4. The time between re-applying teflón applications varies from *6 to *12 hours of production depending on oven length, speed, temperature, slat belt condition, product size and weight, etc.



INGREDIENTS: polydimethyl siloxane, emulsifier, sodium benzoate and water

Precautionary Statements: P305+P338, P351, P301+P330+331

Hazard Statement: None specific



Accidental eye contact: Rinse thoroughly with water for several minutes. Remove contact lenses, if present and continue rinsing.

Available in 2-5 liter jugs, 5 US Gal. pails (18.9 L.) & 55 US Gal. drums (208 L.)

SAFETY FIRST RECOMMENDED PPE

PERSONAL PROTECTIVE EQUIPMENT



Distributed by: Tortillaworld, Inc.

P.O. Box 346

Plainfield, Illinois, 60544

1-800-335-Tortilla (8678) ext. 101

Direct/WhatsApp: 773-882-2308

www.tortillaworld.com

