TortillaTek®

Ready-To-Use Graphite based oven chain lubricant



PRODUCT DESCRIPTION:



TortillaTek® eco-friendly Ready-To-Use (RTU) water based graphite oven chain lubricant was developed specifically to meet the needs of tortilla, wraps, flat-bread & chapatti manufactures, etc. eliminate squeaky and noisy slat belt chains by inhibiting friction without producing smoke when applied, reducing maintenance time and replacement costs while providing superior protection with no taste or odor

INSTRUCTIONS:



SHAKE WELL BEFORE USING

- 1. Shake the 5 gallon pail. Pour into a plastic ½ gallon/64 oz. container or similar. Stir and apply using a common 1½ or 2" paint brush
- 2. To prevent graphite from smoking. DO NOTAPPLY WHEN OVEN IS HOT. Apply when oven temperature is between 50°F & 200°F (98°C)
- 3. Re-applying graphite applications depends on oven size, speed, temperature, etc. It varies from every *8 to *20 hours of production or as needed to eliminate squeaky slat belt chains.

INGREDIENTS: graphite, water, polyethylene glycol, carbomer and preservatives

Hazard Statements: H320, causes eye irritation

Precautionary Statements: P102, P301, P305+P351+P338, P264, P362,

301+P301+P330+P331, P312, P304+340, P402+404, P502

Accidental eye contact: Rinse thoroughly with water for several minutes. Remove contact

lenses if present and continue rinsing

Available in 5 US Gal. pails (18.9 L.)

SAFETY FIRST RECOMMENDED PPE PERSONAL PROTECTIVE EQUIPMENT









Distributed by: Tortillaworld, Inc. P.O. Box 346 Plainfield, Illinois, 60544 1-800-335-Tortilla (8678) ext. 101 Direct/WhatsApp: 773-882-2308 www.tortillaworld.com

















